

Model information about cooker hoods

Miele						
Model name/ model ID number			DA249-4			
Configuration						
Vented/Recirculation			● / –			
Convertible for recirculation operation			–			
Rear wall fixing			●			
Ceiling fitting			–			
Housing unit fitting top/bottom/side			– / – / –			
Dimensions						
Product dimensions	Height	cm	–			
	Width	cm	90,0			
	Depth	cm	50,0			
Unit height including chimney piece	Vented	cm				
	Recirculation	cm				
Niche dimensions for assembly	Height	cm				
	Width	cm				
	Depth	cm				
Depth		cm				
Minimum		cm	45,0			
Minimum distance above gas hob		cm				
Features						
Vent connection top/rear/side ¹⁾			● / ● / –			
Vent connection diameter			mm	150		
Non-return flap in unit			● /			
Fan adjustable infinitely/in stages (no.)			– / –			
Intensive setting ²⁾			–			
Flow rate ³⁾						
Vented from – To	m³/h		200 - 400	-	-	-
Recirculation from – To	m³/h		150 - 330	-	-	-
Intensive setting vented/recirculation	m³/h		640 / 490	/	/	/
Net weight ⁴⁾	kg		22,5			
Electrical specifications						
Voltage	V		230			
Wattage	W		240			
Fuse	A		10			
Connection cable length	cm		150			
Earthed plug/Fixed connection			● / –			
Interference suppressed			●			
Mains interference free			●			
Name and address of supplier			Miele & Cie. KG, Postfach, 33325 Gütersloh			
Note:						
• Yes, available						
1) Precise dimension						
2) Short-term high ventilation rate in conjunction with higher noise level						
3) Depending on external fan						
4) When fitting under a wall unit or on the wall/ceiling, ensure that the wall unit and the wall/ceiling can support the weight of the cooker hood (including decor front if appropriate).						
Note: Table established 07/05. Subject to further development.						